

Air Impact Wrench 1"



Handle Exhaust
GW-38R



GW-55T

SPECIFICATIONS

Model	Square Drive (inch)	Bolt Capacity (mm)	Max. Torque ft.lb (Nm)	Net Weight (kg)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm)	Sound Pressure (dBA)	Vibration (m/S ²)	Mechanism
GW-38R	1"	38	1,400 (1,900)	9.60	300	0.58	1/2"	13	89	3.5	One Hammer
GW-55T	1"	50	2,500 (3,390)	16.40	628	1.82	1/2"	13	104	7.2	Twin Hammer

Air Impact Wrench 3/4"



GW-22N1



GW-24D

SPECIFICATIONS

Model	Square Drive (inch)	Bolt Capacity (mm)	Max. Torque ft.lb (Nm)	Net Weight (kg)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm) I.D.	Sound Pressure (dBA)	Vibration (m/S ²)	Mechanism
GW-22N1	3/4"	27	750 (1,018)	4.80	240	0.30	1/4"	8	95	3.4	Pin Clutch
GW-24D	3/4"	27	800 (1,085)	4.90	248	0.30	1/4"	8	88	3.5	Pin Clutch

Air Impact Wrench 1/2"



GW-11T



GW-15B



GW-17T



GW-18D



GW-19R

SPECIFICATIONS

Model	Square Drive (inch)	Bolt Capacity (mm)	Max. Torque ft.lb (Nm)	Net Weight (kg)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm) I.D.	Sound Pressure (dBA)	Vibration (m/S ²)	Mechanism
GW-11T	1/2"	16	190 (258)	1.37	140	0.20	1/4"	6.5	90	2.9	Twin Hammer
GW-15B	1/2"	16	230 (312)	2.45	178	0.22	1/4"	6.5	98	4.1	One Hammer
GW-17T	1/2"	16	350 (475)	1.50	142	0.20	1/4"	6.5	85	2.7	Twin Hammer
GW-18D	1/2"	16	380 (515)	2.70	190	0.22	1/4"	6.5	88	2.8	Pin Clutch
GW-19R	1/2"	18	430 (588)	2.67	175	0.23	1/4"	6.5	83	2.7	Twin Hammer

Air Impact Wrench 3/8"



GW-10T



GW-12C

SPECIFICATIONS

Model	Square Drive (inch)	Bolt Capacity (mm)	Max. Torque ft.lb (Nm)	Net Weight (kg)	Length (mm)	Air Cons. (m ³ /min)	Air Inlet (inch)	Hose Size (mm) I.D.	Sound Pressure (dBA)	Vibration (m/S ²)	Mechanism
GW-10T	3/8"	13	190 (258)	1.16	135	0.30	1/4"	6.5	90	2.9	Twin Hammer
GW-12C	3/8"	13	200 (271)	1.50	155	0.20	1/4"	6.5	88	2.8	Jumbo Hammer